

# CARBON FEET PRINT

The confection of low temperature recycling asphalt at  $\geq 248^{\circ}\text{F}$  /  $120^{\circ}\text{C}$  of repaved asphalt with GREENSEAL AR reduces combustion with less smoke, and finally promoting favourable carbon footprint values for the plant and, the asphalt.

## CARBON FOOT PRINT

(based on the values from the producers of the substances used in GREENSEAL AR)

Greenseal	* + Cfp /CO2 e/kg	** - Cfp:CO2 e/kg..	*** Net – Cfp result CO2 e/kg
Type E	+0,492	-1,463	--0,971

\* +Cfp values for ::- transport raw materials to the yard, production process , confection storage and transport from our suppliers 'substances to :our shaping and tolling ( IBC) company, and trader, note : no available Cfp values for shaping and tolling.

Biogenic carbon released

\*\* -The photosynthesis with CO2 captation from the atmosphere during the pinetree life, is fixed by EN-ISO 14967-2018 –EN 16785-1-2015 according LCA-14040-14044-Ecoinvent ( version 38-of 21/09/2021-GHG protocol.)

\*\*\*Greenworld expects that the use of their substances with negativ Cfp values in the GREENSEAL AR contributs to the assimilation of a friendly ecological label.

---